


DATA SHEET

DCW AM 50 50

RUGGED ANTENNA


Deltenna Limited
 9 Forest Gate, Pewsham, Chippenham,
 Wiltshire, SN15 3RS, United Kingdom
 Tel +44 (0)1249 450 910 Fax +44 (0)1249 656549
info@deltenna.com www.deltenna.com



Wide Band	824MHz – 960MHz
Polarisation	CP
Azimuth Half Power Beamwidth	50
Elevation Half Power Beamwidth	50
Fixed Electrical Tilt	0

Mechanical Specifications	
Input	1 x SMA female
Connector Position	Rear
Weight	
Wind Load	40N
Max. wind velocity	130Km/h
Packing Size	NA
Height/width/depth	315/315/40 mm

Type No	DCW AM 50 50
Frequency Range	824 - 960 MHz
Polarisation	Circular
Gain	10dBi @ 960MHz
Axial Ratio	<3dB
Azimuth Half Power beam width Copolar	50 degrees +/- 5 degrees
Elevation Half Power beam width Copolar	50 degrees +/- 5 degree
Fixed Electrical tilt options #	0 degrees
Sidelobe suppression for firstsidelobe above horizon	NA
Front to back ratio copolar	>20 dB
Cross Polar Ratio on boresight	Typically 20 dB
Isolation: port to port	NA
Impedance	50Ω
VSWR	<2:1
Max power per input	20 Watts at 50 degrees ambient temperature



Radome available in any standard RAL colour by request

UNIVERSAL FIELD MOUNTABLE BRACKET

